

Thank you for purchasing the F-20 Tigershark EDF RxR.

F-20 Tigershark EDF Rx-R™

Please use this addendum in conjunction with the included ARF manual to complete assembly of the model. Some steps in the build section of the manual have already been completed for you.

This addendum includes all the assembly steps in the manual that can be **omitted** as well as any **additional** steps that need to be performed. Unless noted in this addendum, follow the steps in the ARF manual in the order in which they are written.

STEP

1 -

On page 3 of the manual in the DECISIONS YOU MUST MAKE section, (3) servos have been preinstalled in the model and do not need to be purchased separately. An ESC is also preinstalled in the fuselage and does not need to be purchased separately. Adhesives and building supplies will still be necessary for the completion of the model.

2 >

On page 7 of the manual, the EDF FAN PREPARATION & INSTALLATION section can be skipped as it has already been completed for you.

3 -

On page 8 of the manual in the INSTALL THE RADIO GEAR section, steps 1-6 can be skipped as they have already been completed for you. If you are installing a 72MHz receiver, you must still route the antenna tube through the upper channel as described in step 6.

4 >

On page 9 step 8, the ESC has already been installed inside the fuselage. The receiver will still need to be installed as described in step 8.

5

On page 9 step 3, the 1 x 130mm wire pushrod should be installed into the inner hole of the elevator servo arm. The inner hole does not need to be enlarged with a drill bit as that has already been done for you.



On page 10 step 4, the 1 x 60mm wire pushrods should be installed into the inner holes of the aileron servo arms. These holes do not need to be enlarged as that has already been done for you.

